



PROPERTY	DESCRIPTION
Primary Yarn Polymer	Polyethylene; Polypropylene
Yarn Cross Section	Polyethylene Slit Film; Texturized Polypropylene
Standard Color	Field; Terra Cotta
Additional Colors Available	White
UV Stabilized	Yes
Fabric Construction	Tufted
Primary Backing	Dual layered woven polypropylene
Coating Type	SilverBack™ Polyurethane
Perforations	Yes
Polyethylene Yarn Denier/Ends	8000/1 (Slit) 4600/8 (Texturized PP)
Infill	Preferred Infill
Pile Height	1 3/4"
Pile Weight	46 oz.



## APPLICATION

This is a field product. This product should be installed outdoors on a compacted aggregate base. Custom designed for baseball, Fielder's Choice has the added durability designed to reduce infill splash and migration which is extremely important in gameplay.

**TESTING**
**Fielder's Choice 46**

<b>FINISHED FABRIC</b>	<b>ENGLISH</b>	<b>SYSTEM</b>	<b>METRIC</b>	<b>SYSTEM</b>	<b>ASTM TEST</b>
<b>Nominal Specification</b>	<b>Value</b>	<b>Units</b>	<b>Value</b>	<b>Units</b>	<b>Method</b>
<b>Pile Height (Nominal)</b>	1 3/4	In.	44.45	mm.	D-5823
<b>Face Weight</b>	46	oz/yd	1559	g/m	D-5848
<b>Total Fabric Weight</b>	73	oz/yd	2475	g/m	D-5848
<b>Primary backing Weight</b>	7.4	oz/yd	251	g/m	D-5848
<b>Secondary Coating Weight</b>	20	oz/yd	678	g/m	D-5848
<b>Tuft Bind</b>	>10	lbs.	>4.5	Kg.	D-1335
<b>Grab Tear Strength (Average)</b>	>200	lbs.	>91	Kg.	D-2256
<b>Lead Content</b>	<50	ppm	<50	ppm	D-2765
<b>Total Yarn Linear Density</b>	12,600	Denier	14,000	D-Tex	D-1577
<b>Tensile Strength (Slit PE)</b>	8	lbs.	3.63	Kg.	D-5034
<b>Tensile Strength (Texturized PP)</b>	3.7	lbs.	1.7	Kg.	D-789
<b>Stitch Rate</b>	10.5	Per 3"	13.755	Per 10 cm	D-5793
<b>Machine Gauge</b>	1/2	In.	1.27	Cm.	D-5793
<b>Flammability</b>	TEST	PASSED	TEST	PASSED	D-2859
<b>Water Permeability w/infill</b>	>30	In./Hr.	>30	Cm./Hr.	F-1551
<b>Fiber Thickness (Slit PE)</b>	9.4	mils	100	microns	D-3218
<b>Fabric Width</b>	15	Ft.	4.6	M	None

