

## **TURF SUPPLIERS**

## INSTALLATION

A DIVISION OF ALL SURFACE PRODUCTS



#### **FAST GRASS 740**

PROPERTY	DESCRIPTION
Primary/Stalk Yarn Polymer	52% Polyethylene
Secondary/Thatch Yarn Polymer	48% Nylon
Yarn Cross Section	Polyethylene Slit-Film/Texturized Nylon
Standard Colors	Field Green; White
UV Stabilized	Yes
Fabric Construction	Tufted
Primary Backing	Dual layered woven polypropylene
Coating Type(s)	SilverBack™ Polyurethane or 5mm Polyurethane Foam w/fleece
Perforations	Custom Only
Polyethylene (Slit-Film) Yarn Denier/Ends	5040/1
Texturized Nylon Denier/Ends(Thatch)	4400/8
Infill	N/A
Pile Height	3/4"
Pile Weight	40 oz.

#### **APPLICATION**

This non-rubber infilled turf has all the advantages of previous generations and perform even higher in wear and resistance tests. The blend of nylon and polyethylene is an almost perfect 50/50 combination. This gives you the true ball roll of a traditional nylon field, with the softness of the new generation rubber-filled turf. No rubber infill makes maintenance easier, and up to 10% cooler. These systems can also be portable with added 4" or 8" velcro.















\*Custom colors available upon request



# TURF SUPPLIERS

## INSTALLATION

A DIVISION OF ALL SURFACE PRODUCTS

FINISHED FABRIC	ENGLISH	SYSTEM	METRIC SYSTEM		ASTM TES
Iominal Specification	Value	Units	Value	Units	Method
ile Height (Nominal)	.75	In.	1905	mm.	D-5823
ace Weight	40	oz/yd²	1356	g/m²	D-5828
otal Fabric Weight (8mm Foam)	160	oz/yd²	5425	g/m²	D-5828
otal Fabric Weight (SilverBack™)	67	oz/yd²	2271	g/m²	D-5828
rimary backing Weight	7.4	oz/yd²	251	g/m²	D-5828
econdary Coating Weight (Foam)	113	oz/yd²	3831	g/m²	D-5828
econdary Coating Weight (SilverBack <sup>†</sup>	™) 20	oz/yd²	678	g/m²	D-5828
uft Bind	>8	lbs.	>3.6	Kg.	D-1335
Grab Tear Strength (Average) Lead	>200	lbs.	>91	Kg.	D-2256
Content	<50	ppm	<50	ppm	D-2766
otal Yarn Linear Density	9,400	Denier	10,445	D-Tex	D-1577
ensile Strength	8.0	lbs.	3.63	Kg.	D-5034
titch Rate	13	Per 3"	17	Per 10 cm	D-5793
1achine Gauge	1/4	In.	0.95	Cm.	D-5793
lammability	TEST	PASSED	TEST	PASSED	D-2859
Vater Permeability w/infill	>30	In./Hr.	>76	Cm./Hr.	F-1551
iber Thickness	9.4	mils	100	microns	D-3218
abric Width	12.00	Ft.	3.60	М	None



It is the policy of Turf Suppliers to continuously improve their line of products. Therefore, Turf Suppliers reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.