



GAMECHANGER 46Q - FL420-46

| PROPERTY | DESCRIPTION | | |
|-------------------------------|--|--|--|
| Primary Yarn Polymer | Polyethylene | | |
| Yarn Cross Section | Polyethylene Monofilament; Polyethylene Slit Film | | |
| Standard Color | Field; Field/Lime | | |
| Additional Colors Available* | White, Yellow, Red, Florida Blue, Black, Orange, Terra Cotta | | |
| UV Stabilized | Yes | | |
| Fabric Construction | Tufted | | |
| Primary Backing | Dual layered woven polypropylene | | |
| Coating Type | SilverBack™ Polyurethane | | |
| Perforations | Yes | | |
| Polyethylene Yarn Denier/Ends | 1800x4 (Mono) 5000/1 (Slit) | | |
| Recommended Infill | Per Specification | | |
| Pile Height | 2 1/4" | | |
| Pile Weight | 6 oz. | | |

APPLICATION

This is a multi sport field product. This product should be installed outdoors on a compacted aggregate base. The GameChanger series is the world's first tufted fabric utilizing 3 ends per needle. The 3C "Triple Coverage" system allows for more face yarn to show off its beautiful colors. This 12,200 denier system will keep your field looking newer, longer with over 50% more yarn denier above the rubber infill.



*Custom colors available upon request

778.323.0000 | sales@turfsupplierscanada.com | turfsupplierscanada.com



INSTALLATION

A DIVISION OF ALL SURFACE PRODUCTS

| FINISHED FABRIC | ENGLISH | SYSTEM | METRIC | SYSTEM | ASTM TEST |
|-----------------------------------|---------|---------|--------|-----------|-----------|
| Nominal Specification | Value | Units | Value | Units | Method |
| Pile Height (Nominal) | 2 1/4 | In. | 57.15 | mm. | D-5823 |
| Face Weight | 46 | oz/yd² | 1560 | g/m² | D-5848 |
| Total Fabric Weight | 75 | oz/yd² | 2542.5 | g/m² | D-5848 |
| Primary Backing Weight | 7.4 | oz/yd² | 251 | g/m² | D-5848 |
| Secondary Coating Weight | 22 | oz/yd² | 746 | g/m² | D-5848 |
| Tuft Bind | >10 | lbs. | >3.6 | Kg. | D-1335 |
| Grab Tear Strength (Average) | >200 | lbs. | >91 | Kg. | D-2256 |
| Lead Content | <50 | ppm | <50 | ppm | D-2765 |
| Total Yarn Linear Density | 12,200 | Denier | 13,554 | D-Tex | D-1577 |
| Tensile Strength (Mono) | 16 | lbs. | 7.26 | Kg. | D-5034 |
| Tensile Strength (Slit) | 8 | lbs. | 3.6 | Kg. | D-789 |
| Stitch Rate | 8.5 | Per 3" | 11.14 | Per 10 cm | D-5793 |
| Machine Gauge | 1/2 | In. | 1.27 | Cm. | D-5793 |
| Flammability | TEST | PASSED | TEST | PASSED | D-2859 |
| Water Permeability w/infill Fiber | >30 | In./Hr. | >76 | Cm./Hr. | F-1551 |
| Thickness (Mono) | 22.0 | mils | 310 | microns | D-3218 |
| Fiber Thickness (Slit) | 9.4 | mils | 100 | microns | D-3218 |
| Fabric Width | 15 | Ft. | 4.6 | М | None |



It is the policy of Turf Suppliers to continuously improve their line of products. Therefore, Turf Suppliers reserves the right to change, modify or discontinue systems, specifications and accessories of all products at any time without notice or obligation to purchaser.

778.323.0000 | sales@turfsupplierscanada.com | turfsupplierscanada.com